



## TECHNICAL DATA SHEET CLEAR PROTECTIVE TOP COAT

Clear Protective Top Coat is a water based 100% acrylic clear protective final top coat that can be used over our membranes to improve gloss and colour retention. It is suitable for a variety of substrates including concrete roof surfaces, terracotta roof tiles, as well as metal, zincalume and Colorbond® roof surfaces.

Application extends the material warranty of our topcoats by two (2) years.

### APPLICATION & USAGE:

Gloss Level	High Gloss	Tip Size	517
Touch Dry   Overcoat	30 mins   2 hours	Coverage	10m <sup>2</sup> per litre
Wash Up	Water	Thinner	Not Recommended
Full Cure	14 days	Drinking Water Safe	After 14 days curing & thoroughly washed

The above figures are based on 25°c and 50% relative humidity. Do not over apply this product. Heavy application or any moisture present at the time of application may cause a milky appearance and/or failure of the coating. Exposure to dew may also affect the performance.

Clear Protective Top Coat must be applied within two weeks of membrane application.

### HEALTH & SAFETY:

May cause an allergic skin reaction. Harmful to aquatic life. Keep out of reach of children. Read label before use. Avoid breathing gas, mist, vapours, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Avoid release to the environment.

**FIRST AID:** For advice, contact a Doctor or Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) and have the product container or label at hand. See SDS for more information.

**Ingestion:** If swallowed, rinse mouth with water. Give a glass of water. If vomiting occurs, give further water. Contact a poisons information centre or doctor for advice.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering, or irritation occurs, seek medical advice.

**Inhalation:** If inhaled, remove from contaminated area into fresh air. Remove contaminated clothing. Allow patient to assume a comfortable position. Keep warm and at rest until fully recovered. If symptoms develop seek medical advice.

**Eye Contact:** If in eyes, hold eyelids apart and immediately flush the eye continuously with running water for 15 minutes. If irritation occurs, seek medical advice.

**FIRE:** If material is involved in a fire use water fog, foam, or dry agent.

**STORAGE & DISPOSAL:** Store in a cool, well-ventilated place away from sunlight and oxidising agents. Dispose of contents/container in accordance with local, regional, national, and international regulations.

### RECOMMENDATIONS & PRECAUTIONS:

Use this product in a well-ventilated area. Ensure that the application is in accordance with our recommendations.

We recommend working conditions of between 10°c and 35°c. In temperatures over 35°c Hot Weather Additive may be required.

Due care and consideration should be taken where water collection methods are present. We recommend allowing 14 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.

The surface preparation is the responsibility of the Builder, Renovator, Contractor, or Applicator. It is also the responsibility of the Applicator to ensure that the substrate is of an acceptable standard prior to the application of Roof Top Restore Coatings.

### DISCLAIMER:

The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use of our product is beyond our control. We recommend that the applicator of this product conducts a small test patch in an inconspicuous area to determine the suitability of the material and its recommendations prior to use or application.