



## TECHNICAL DATA SHEET ROOFLEX HEAT REFLECTIVE

Rooflex Heat Reflective uses technology to reflect the sun's radiation away from the roof surface and is recommended and used as a protective coating that can be brushed, rolled, or sprayed to the following surfaces:

- Concrete and Terracotta Roof Tiles
- Metal Roof Surfaces including Colorbond®
- Fibro Cement Sheeting.

It provides a durable colour fast coating system that significantly reduces dirt accumulation, pollution, and chemical attack.

### APPLICATION & USAGE:

Gloss Level	Gloss or Satin	Tip Size	519 - 521
Touch Dry   Overcoat	30 mins   2 hours	Coverage	5m <sup>2</sup> per litre
Wash Up	Water	Thinner	Not Recommended
Full Cure	14 days	Drinking Water Safe	After 14 days curing & thoroughly washed

The above figures are based on 25°c and 50% relative humidity. Please note that Rooflex Heat Reflective is only suitable on high glaze terracotta tiles when Terracotta Primer has been applied.

### HEALTH & SAFETY:

May cause an allergic skin reaction. Harmful to aquatic life. Keep out of reach of children. Read label before use. Avoid breathing gas, mist, vapours, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Avoid release to the environment.

**FIRST AID:** For advice, contact a Doctor or Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) and have the product container or label at hand. See SDS for more information.

**Ingestion:** If swallowed, rinse mouth with water. Give a glass of water. If vomiting occurs, give further water. Contact a poisons information centre or doctor for advice.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering, or irritation occurs, seek medical advice.

**Inhalation:** If inhaled, remove from contaminated area into fresh air. Remove contaminated clothing. Allow patient to assume a comfortable position. Keep warm and at rest until fully recovered. If symptoms develop seek medical advice.

**Eye Contact:** If in eyes, hold eyelids apart and immediately flush the eye continuously with running water for 15 minutes. If irritation occurs, seek medical advice.

**FIRE:** If material is involved in a fire use water fog, foam, or dry agent.

**STORAGE & DISPOSAL:** Store in a cool, well-ventilated place away from sunlight and oxidising agents. Dispose of contents/container in accordance with local, regional, national, and international regulations.

### RECOMMENDATIONS & PRECAUTIONS:

Use this product in a well-ventilated area. Ensure that the application is in accordance with our recommendations.

We recommend working conditions of between 10°c and 35°c. In temperatures over 35°c Hot Weather Additive may be required.

Due care and consideration should be taken where water collection methods are present. We recommend allowing 14 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.

The surface preparation is the responsibility of the Builder, Renovator, Contractor, or Applicator. It is also the responsibility of the Applicator to ensure that the substrate is of an acceptable standard prior to the application of Roof Top Restore Coatings.

### DISCLAIMER:

The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use of our product is beyond our control. We recommend that the applicator of this product conducts a small test patch in an inconspicuous area to determine the suitability of the material and its recommendations prior to use or application.